

SD1 Desktop Kit 250

SD1 Desktop
Kit 250

SOUNDTUBE
ENTERTAINMENT



Specifications: SD1 Desktop Kit 250

Mounting hardware included

Nominal Impedance	8 ohm
Impedance (min)	7.8 ohm
Sensitivity dB @ 2.83V/1M	70 - 75 dB
Sensitivity dB @ 1W/1M (2)	73.5 dB
Frequency Response (± 3 dB)	80 Hz - 10 kHz Nominal w/o EQ
Frequency Response (± 10 dB)	60 Hz - 15 kHz Nominal w/o EQ
Max. Program Power	100W
Max. Continuous Power RMS	30W
Max. Power SPL @ 1 M	88.5 dB
Coverage Angle (-6 dB @ 10 kHz)	120
Angle	120
Coverage Angle (-6 dB @ 2 kHz)	120
Inputs	Wire lead with screw connector block
Height (SM = Height)	52.34 mm / 2.06 in
Diameter (SM = Width)	58.60 mm / 2.30 in
Backcan Diameter	51 mm / 2.05"
Weight	.67 kg / 1.5 lbs
Shipping Weight	/ 4.3 lbs
Packaging	1 per box
Regulatory - RoHS	approved

SD1 Desktop Kit 250

SD1 Desktop
Kit 250

SOUNDTUBE
ENTERTAINMENT

Description

The SolidDrive SD1 Desktop Kit-250 is the ideal way to see how the SolidDrive works on any surface. The SolidDrive unit in the kit has a special silicon backing so it will work with virtually any surface without scratching or leaving a mark. The kit is also includes the SD-250 amplifier. This is a 50 watts rms per channel amplifier that can run in stereo, mono, or bridged with balanced or unbalanced inputs. But most importantly it has custom electronic EQs for glass, sheet rock, wood, or bypass. Having the correct power and the right EQ will make the AD sound its best.

Patented SoundTube Technologies

SoundTube and MSE Audio Group constantly develop new technologies that enhance audio product performance. SoundTube innovations are protected by multiple U.S. and international patents, which explicitly cover SoundTube dispersion, enclosure and dome technologies. MSE

Audio Group actively defends its patents in order to protect SoundTube resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified

by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

SoundTube

8005 W. 110th St. | Suite 208
Overland Park, KS 66210
Phone 9136635600
Fax 8556635600
Toll Free 8556635600
<http://soundtube.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

SD1 Desktop Kit 250

SD1 Desktop
Kit 250

SOUNDTUBE
ENTERTAINMENT

Included Accessories

SD-250 Amplifier



Passive EQ Modules