



Specifications: P3-35

Mounting hardware included

Max Gain	34 dB (8 ohms)
Power Output	2 Channel - 50 watts RMS/CH >1% @ 8 ohms, 55 watts @ 4 ohms; 3 Channel - 35 watts RMS/CH >1% @ 8 ohms, 40 watts @ 4 ohms
Power Requirements	Input: 100-240VAC 50/60 Hz, UL-CUS, FCC, CE, TUV, SUD, PSB, PSE; Output: 32VDC@ 3.75A
Signal to Noise Ratio	Better than 84 dB unweighted
Amp Power	2 Channel - 50 watts RMS/CH @ 8 ohms, 55 watts @ 4 ohms; 3 Channel - 35 watts RMS/CH @ 8 ohms, 40 @ 4 ohms, THD >.1% 10 Hz - 20 kHz below rated output
Max Current Consumption 120V	Input: 100-240VAC 50/60 Hz, 1.7A
Inputs	Stereo Mini Analog. Optical Digital, Bluetooth
Height (SM = Height)	31.75 mm / 1.25 in
Diameter (SM = Width)	99.06 mm / 3.9 in
Weight	0.42 kg / 0.93 lb
Packaging	One Per Box
Regulatory - UL	60065
Regulatory - CE	approved
Regulatory - RoHS	Approved
Regulatory - IP	Approved
Regulatory - Other	ETL-C/US, FCC, CE, TUV, SUD, PSB, PSE Approved

Description

Phase Technology's P3-35 mini-amp is a powerful and feature-rich amplifier in a small package.

The P3-35 features digital and analog inputs, Bluetooth® functionality (so you can stream content right from your smart phone), IR learning (so you can program your television remote to control the amp's volume), and even a line-level subwoofer output option, allowing you to integrate any powered subwoofer into your set-up. The P3-35 even features Dolby Digital® decoding, ensuring that you'll never lose the surround content in any Dolby Digital mixes.

The P3-35 amp measures only 1 ¼" by 4", so its small enough to fit behind a wall mounted TV and, when paired with any of Phase Technology's ultra-thin Teatro speakers, will create the perfect installation scenario for this powerful and feature-rich mini-amplifier.

Patented SoundTube

Technologies

SoundTube and MSE Audio Group constantly develop new technologies that enhance audio product performance. SoundTube innovations are protected by multiple U.S. and international patents, which explicitly cover SoundTube dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect SoundTube resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers

SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

SoundTube

8005 W. 110th St. | Suite 208
Overland Park, KS 66210
Phone 9136635600
Fax 8556635600
Toll Free 8556635600
<https://soundtube.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

P3-35

3-Channel Amplifier

SOUNDTUBE
ENTERTAINMENT
